

EM6500S2C



- 1 Portable power with premium features and traditional Honda durability and performance
- 1 6500 watts maximum AC output
- 1 Home backup and Commercial usage (for non-GFCI applications)
- 1 Suitable for rental applications



SPECIFICATIONS

MAXIMUM AC OUTPUT (WATTS)	6500	FUEL TANK CAPACITY (LITRES)	23.5
AC Voltage Available	120/240	TRANSPORT WHEELS	2 Wheel standard
MAXIMUM CONTINUOUS AC OUTPUT (WATTS)	5,500 7,000 (iAVR)	LIFTING HOOK	Optional (P/N 06810-Z22-A30ZA)
Max. Rated AC Amperage @ 120 V/240 V	45.8/22.9 (58.3/29.2 for 10 sec. iAVR)	BATTERY	Standard (P/N 31500-MCR-J01)
GROUND FAULT CIRCUIT INTERRUPTER (GFCI)	-	Approximate Running Time/Tankful (hrs)	6.9** / 10.4***
FREQUENCY (HERTZ)	60	Rated Fuel Consumption (Litres/Hour)	3.40**
AUTOMATIC VOLTAGE REGULATOR	Standard iAVR (Intelligent Automatic Voltage Regulator)	Noise Level dB(A) (1.5 m to 7 m)	73**
DC Output Volts/Amps	12/8.0	Length (Without Handles and Wheels)	681 mm (26.8 in.)
Engine Type	Honda iGX390T2 OHV, 4-stroke, air-cooled	Length (With Handles and Wheels)	1,051 mm (41.4 in.)
DISPLACEMENT	389 cc	Width (Without Handles and Wheels)	530 mm (20.9 in.)
STARTING SYSTEM	Electric/recoil	Width (With Handles and Wheels)	706 mm (27.8 in.)
Low Level Oil Alert System	Standard	Height (Without Lift-Hook)	719 mm (28.3 in.)
AUTO THROTTLE	Standard	Height (With Lift-Hook)	773 mm (30.4 in.) Optional lift hook
REMOTE START CAPABILITY	Optional	DRY WEIGHT	104.8 kg (231.0 lb.)
REMOTE START KIT PART NUMBER INFO	06610-Z22-800ZA (10M)	COLD CLIMATE TECHNOLOGY	Standard
		Common Duplex Receptacle Specifications	40 amps/120 VAC continuous is available as combined total from these twin duplex AC receptacles. Maximum of 20 amps available from each GFCI duplex receptacle.

Models and/or colours may not be exactly as shown. Errors and omissions excepted. Specifications are subject to change without notice. See your Honda Power Equipment dealer for details.

For optimum performance and safety, please read your owner's manual before operating your Honda product. Always wear the appropriate safety gear when operating your Honda.

©/TM — Trademarks of Honda Canada Inc. or used under licence from Honda Motor Co., Ltd. or third parties.

Your Dealer: **Timberland Supply Co. Ltd.**
1520 Lorne St.
Kamloops, BC, V2C 1X6
(250) 372-9561 / (800) 563-5223
www.timberland-supply.com