

F501K2C2



The F501 mid-tine tillers feature a GX160 4-stroke overhead valve Honda engine that offers enough power to tackle your large residential lots. Available in a 24-inch (60 cm) (F501K2C1), or a 36-inch (91.4 cm) (F501K2C2) tilling width model with adjustable handles for increased operator comfort, these tillers are designed with commercial-grade construction for durability and reliability on even the toughest ground.

Features

- Honda GX160 OHV 4-stroke mini engine
- Ergonomically arranged controls for safe, convenient operation
- Three-way adjustable handlebar
- Narrow transmission case allows deeper tilling
- 2 forward and 1 reverse transmission speed
- Adjustable depth bar allows tilling at pre-set depths
- Quick-release clutch lever stops tines immediately upon release
- Standard tine extensions on the F501K2C2 allow a wide 36" tilling path

Specifications

Tiller Type	Mid Tine
Engine Type	4-stroke, OHV
Honda Engine Model	GX160
Displacement	163 cc (10.0 CID)
Fuel Capacity	2.60 Litres (0.60 Imp. gal)
Recommended Fuel	Regular unleaded gasoline (87 Octane)
Starting System	Recoil starter
Air Cleaner	Dry paper type
Muffler Heat Protector	Standard
Lubrication System	Splash
Folding Handle	N/A
3-position Handle Adjustment	Standard
4-position Handle Adjustment	N/A
Transport Wheels	Standard
Adjustable Depth Bar	Standard
Tilling Width	91.4 cm (36.0 in)
Tine Diameter	28.0 cm (11.0 in)
Tine Speed @ Max. Torque Speed	114 RPM
Transmission Type	Chain drive
Transmission Speed(s)	2-Forward / 1-Reverse
Overall Length	132.0 cm (52.0 in)
Overall Height	99.5 cm (39.2 in)
Overall Width	95.5 cm (37.6 in)
Dry Weight	61.0 kg (134.5 lb)

Accessories

Furrow Kit	•
Wheel Weight Kit	—
Side Disc Kit	Standard
Lawn Aerator Kit	—
Walkway Border/Edger Kit	—
Lawn Dethatcher Kit	—
Digging Tine Kit	—

• Available as an optional accessory on this model.

Your Dealer:

Timberland Supply Co. Ltd.
1520 Lorne Street
Kamloops, BC, V2C 1X6
(250) 372-9561 / (800) 563-5223