

HHT25SLTC


The HHT25SLTC and HHT25SUT4C are powered by GX25 mini 4-stroke overhead cam Honda engines. These lightweight and smooth-running trimmers are built with commercial-grade parts and construction throughout.

Features

- 25 cc Honda GX25 OHC Mini 4-stroke engine
- Loop-style handlebar
- Semi-matic line feed (tap and go) trimmer head and plastic guard
- Bevel gear drive
- Single loop shoulder harness and protective eyeglasses included

Your Dealer:

Timberland Supply Co. Ltd.
1520 Lorne Street
Kamloops, BC, V2C 1X6
(250) 372-9561 / (800) 563-5223

Specifications

Engine Type	Mini 4-stroke, OHC, single cylinder air cooled multi-position (360°)
Honda Engine Model	GX25
Displacement	25 cc (1.53 CID)
Bore and Stroke	35 x 26 mm (1.4 x 1.0 in)
Maximum Net Torque	1.0 N-m (0.74 lbf-ft) @ 5,000 RPM
Idle Speed	3,100 ± 200 RPM
Max. no-load RPM** (requires blade barrier)	10,000 RPM
Ignition System	Transistorized flywheel magneto (Electronic)
Spark Plug	CMR5H (NGK)
Cooling System	Forced air
Starting System	Recoil starter
Stopping System	Ignition primary circuit ground
Carburetor	Diaphragm type w/fuel pump
Recommended Fuel	Regular unleaded gasoline (87 Octane)
Fuel Primer	Anti-flood type
Fuel Capacity	0.50 Litre (17.6 fl. Imp. oz)
Fuel Consumption (Approximate)***	0.5 Litre/hr (0.11 Imp. gal/hr)
Clutch Drive Type	Centrifugal twin shoe-clutch
Clutch Size	54 mm (2 1/8 in) diameter
Clutch Engagement	4,200 ± 200 RPM
Air Cleaner	Semi-dry type
Lubrication System	Oil mist
Oil Capacity	80 cc (2.82 fl. Imp. oz)
Recommended Oil	SAE 10W30 API service classification SJ or later
Handle Type	Loop
Throttle Control Type	Two-motion trigger type
Engine Stop Switch	Slide type switch
Cutting Head (Standard)	Semi-matic line feed nylon (Tap & go)
Cutting Head (Optional)	Manual, Pro-tap
Cutting Width	43.2 cm (17.0 in)
Line Type	Ultra-quiet
Cutting Line Diameter	2.41 mm (0.095 in)
Anti-vibration System	Standard
Drive Shaft Type	Flexible steel cable
Final Drive Gear Case	Helical cut bevel gears / Sealed ball bearings
Gear Ratio	1.235 input shaft: 1 (Output shaft)
Main Pipe Diameter	25.4 mm (1.0 in)
Main Pipe Thickness / Material	1.5 mm (.06 in) / Aluminum
Trimmer Guard with Cutter	Standard
Steel Blade Guard	Optional
Shoulder Harness	Standard
Professional Double Loop Harness	Optional†
Safety Goggles (A.N.S.I std.)	Standard
Blade	Opt. (4-T x 22.9 cm / 9.0 in) steel brush cutting††
Blade Barrier Kit‡	Optional†
Overall Length with Cutter Mounted	188.5 cm (74.2 in)
Overall Width	34.5 cm (13.6 in)
Overall Height	26.5 cm (10.4 in)
Dry Weight without Blades	5.90 kg (13.0 lb)