



Honda's infinitely variable Hydrostatic transmission makes it easy to find the right speed for any snow clearing situation and operator preference. A single lever accurately adjusts ground speed without affecting auger rotation speed.

Gas-Assisted Auger Height Adjustment Control allows auger height adjustment during operation. Slight upward or downward pressure on controls accurately angles the auger to skim uneven gravel or interlocking brick surfaces or dig deep to clear smooth asphalt or concrete surfaces. Release of the handle locks the auger in position.

120 volt AC electric start provides an additional level of convenience on the HS1132TCS.

### Features

- Dual-stage, track drive, clears a 32 in/81 cm width
- Honda GX340, OHV, 4-stroke engine
- Variable speed hydrostatic transmission
- Finger tip controlled auger-height adjustment
- 15 m/49 ft. max. discharge; up to 65 metric tons (72 tons)/hr.
- Standard work light
- 120 VAC electric start (HS1132TCS model only)

**Your Dealer:** **Timberland Supply Co. Ltd.**  
 1520 Lorne Street  
 Kamloops, BC, V2C 1X6  
 (250) 372-9561 / (800) 563-5223

### Specifications

## HS1132TC/TCS

Discharge Type	Dual stage
Axle Type	Track drive
Drive Type	Hydrostatic transmission
Speeds	Infinitely variable
Maximum Ground Speed	Forward : 51.0 m/min. (167.3 ft./min)
Clearing Width	81.0 cm (31.9 in)
Intake Housing Height	51.0 cm (20.1 in)
Auger Diameter	35.5 cm (14.0 in)
Auger Type	Steel serrated
Auger Drive	Belt driven shaft
Auger Height Adjustment	Gas assist
Chute Rotation	Remote manual crank
Chute Turning Radius	210°
Deflection Control	Remote manual lever
Chute Material	Steel
Maximum Throw Distance *	17 m (56 ft)
Clearing Snow Volume Capacity (Approximate)*	up to 65 metric tons (72 tons/hr)

### Engine

Engine Type	4-stroke, OHV, single cylinder
Honda Engine Model	GX340
Displacement	337 cc (20.6 CID)
Ignition System	Transistorized
Recoil Starter	Standard
Electric Starter	Standard 120 VAC type (HS1132TCS)
Lubrication System	Forced splash
Oil Capacity	1.1 Litre (38.7 fl. Imp. oz)
Recommended Fuel	Regular unleaded gasoline (87 Octane)
Fuel Capacity	6.0 Litres (1.32 Imp. gal)
Operational Time per Tankful **	2.5 hours

### Dimensions

Wheel/Tire Size	N/A
Overall Length	142.2 cm (56.0 in)
Overall Width	81.0 cm (31.9 in)
Overall Height	102.2 cm (40.2 in)
Dry Weight	120.0 kg (264.6 lb) HS1132TC 123.0 kg (271.2 lb) HS1132TCS

### Accessories

Lighting Coil	Standard
Worklight	Standard

### Warranty

Term	2 year (non-commercial)
------	-------------------------