



Honda's infinitely variable Hydrostatic transmission makes it easy to find the right speed for any snow clearing situation and operator preference. A single lever accurately adjusts ground speed without affecting auger rotation speed.

The HS928TC and HS928TCD models also feature Honda Track Drive – pliable rubber tracks with cleats support the snowblower's weight to give superior traction and extra grip on steep driveways and steps.

Standard work light, electric joystick chute control and 12 volt DC electric start provide an additional level of convenience on the HS928TCD.

Features

- Dual-stage, track drive, clears a 28 in/71 cm width
- Honda GX270, OHV, 4-stroke engine
- Variable speed hydrostatic transmission
- Finger tip controlled auger-height adjustment
- 15 m/49 ft. max. discharge; up to 50 metric tons (55 tons)/hr.
- Standard work light (HS928TCD model only)
- 12 VDC electric start (HS928TCD model only)
- 12 VDC electric chute with joystick control (HS928TCD model only)

Your Dealer: **Timberland Supply Co. Ltd.**
1520 Lorne Street
Kamloops, BC, V2C 1X6
(250) 372-9561 / (800) 563-5223

Models and colours may not be exactly as shown. Specifications subject to change without notice.
 For optimum performance and safety, please read your owner's manual before operating your Honda snowblower.

Specifications

HS928TC/TCD

Discharge Type	Dual stage
Axle Type	Track drive
Drive Type	Hydrostatic transmission
Speeds	Infinitely variable
Maximum Ground Speed	Forward : 51.0 m/min. (167.3 ft./min)
Clearing Width	71.0 cm (28.0 in)
Intake Housing Height	51.0 cm (20.1 in)
Auger Diameter	35.5 cm (14.0 in)
Auger Type	Steel serrated
Auger Drive	Belt driven shaft
Auger Height Adjustment	Gas assist
Chute Rotation	Remote manual crank (HS928TC) Remote electric "Joystick" control (HS928TCD)
Chute Turning Radius	210°
Deflection Control	Remote manual lever (HS928TC) Remote electric "Joystick" control (HS928TCD)
Chute Material	Steel
Maximum Throw Distance *	15 m (49 ft)
Clearing Snow Volume Capacity (Approximate)*	up to 50 metric tons (55 tons/hr)

Engine

Engine Type	4-stroke, OHV, single cylinder
Honda Engine Model	GX270
Displacement	270 cc (16.5 CID)
Ignition System	Transistorized
Recoil Starter	Standard
Electric Starter	Standard 12 VDC type (HS928TCD)
Lubrication System	Forced splash
Oil Capacity	1.1 Litre (38.7 fl. Imp. oz)
Recommended Fuel	Regular unleaded gasoline (87 Octane)
Fuel Capacity	6.0 Litres (1.32 Imp. gal)
Operational Time per Tankful **	2.5 hours

Dimensions

Wheel/Tire Size	N/A
Overall Length	142.2 cm (56.0 in)
Overall Width	72.5 cm (28.5 in)
Overall Height	103.8 cm (40.9 in)
Dry Weight	106.0 kg (233.7 lb) HS928TC 109.0 kg (240.3 lb) HS928TCD

Accessories

Lighting Coil	Standard
Worklight	Standard

Warranty

Term	2 year (non-commercial)
------	-------------------------

*Snow volume capacity and throw distance will vary with individual snow conditions.

** Actual fuel consumption depends on operating load.