



Honda's heavy duty hybrid uses twin variable speed electric motors to control the dual tracks while the powerful GX390 4-stroke OHV engine drives the auger. Dual-stage discharge clears a 91 cm (36 in) path and the DC electric auger height adjuster can be adjusted "on the fly" or set to automatically raise at return path.

Standard work light, 12 volt DC electric start and electric joystick chute control provide the ultimate in convenience and ease-of-use.

Features

- Dual-stage, track drive, clears a 36 in/91 cm width
- Honda GX390, OHV, 4-stroke engine
- Twin, variable speed electric motors / i-Control
- DC electric auger-height adjuster
- 19 m/62 ft. max. discharge; up to 83 metric tons (91 tons)/hr.
- Standard 40 watt work light
- 12 VDC electric start

Your Dealer: **Timberland Supply Co. Ltd.**
 1520 Lorne Street
 Kamloops, BC, V2C 1X6
 (250) 372-9561 / (800) 563-5223

Specifications

HSM1336iC Hybrid

Discharge Type	Dual stage
Axle Type	Track drive
Drive Type	Electric i-Control (24 VDC drive motors)
Speeds	Infinitely variable (Load control)
Maximum Ground Speed	Forward : 50.0 m/min. (164.0 ft./min)
Clearing Width	92.0 cm (36.0 in)
Intake Housing Height	58.0 cm (22.8 in)
Auger Diameter	35.5 cm (14.0 in)
Auger Type	Steel serrated
Auger Drive	Belt driven shaft, electromagnetic clutch
Auger Height Adjustment	Electric auger-height adjuster (Automatic raise at return path)
Chute Rotation	Remote electric "Joystick" control
Chute Turning Radius	240° (Right 110°, left 130°)
Deflection Control	Remote electric "Joystick" control
Chute Material	Steel
Maximum Throw Distance *	19 m (62 ft)
Clearing Snow Volume Capacity (Approximate)*	up to 83 metric tons (91 tons/hr)

Engine

Engine Type	4-stroke, OHV, single cylinder
Honda Engine Model	GX390
Displacement	389 cc (23.7 CID)
Ignition System	Transistorized
Recoil Starter	Standard (Back-up)
Electric Starter	Standard 12 VDC type
Lubrication System	Forced splash
Oil Capacity	1.1 Litre (38.7 fl. Imp. oz)
Recommended Fuel	Regular unleaded gasoline (87 Octane)
Fuel Capacity	6.5 Litres (1.43 Imp. gal)
Operational Time per Tankful **	2.0 hours

Dimensions

Wheel/Tire Size	N/A
Overall Length	165.0 cm (65.0 in)
Overall Width	92.0 cm (36.2 in)
Overall Height	135.0 cm (53.1 in)
Dry Weight	254.0 kg (560.0 lb)

Accessories

Lighting Coil	Standard
Worklight	Standard (24 VDC, 40 watt)

Warranty

Term	2 year (non-commercial)
------	-------------------------