

**HONDA****Power****Equipment**

deluxe transfer WATER PUMPS



These commercial-grade water pumps have extra-thick pump housings, full tubular steel frames and rugged anti-vibration mounts to withstand the rigors of the most demanding job sites.

## Features

- Honda GX160 four-stroke OHV, air cooled, single cylinder
- 76 mm (3") suction and discharge ports
- 1,100 litres per minute maximum discharge (42 Imp. Gal. per minute)
- Oil Alert™ standard
- Full frame, rubber mounted engine and pump

## Specifications

**WB30XK2C**

Pump	Centrifugal
Type	Self-priming
Suction Port Diameter	76 mm /3 in.
Discharge Port Diameter	76 mm /3 in.
Litres per minute	1100
Imp. gal. per minute	42
Litres per hour	66000
Imp. gal. per hour	14520
Total Head	28 m /92 ft.
Suction Head (Total Lift)	8 m /26 ft.
Priming Time @ 5m(16.4 ft.)	150 seconds
Pump Body	Aluminum
Impeller	Cast Iron
Honda Engine	GX160 4-stroke
Type	OHV, air-cooled, single cyl.
Displacement	163 cc
Lubrication System	Splash type
Governor	Mechanical
Starting System	Recoil
Fuel Tank Capacity	3.6 L /0.79 Imp. gal.
Oil Alert	Standard
Drive Unit Type	Direct couple / mech. seal
Frame Type	Full frame
Length	510 mm /20.1 in.
Width	385 mm /15.2 in.
Height	455 mm /17.9 in.
Dry Weight	27 kg /60 lb.

## Your Dealer:

Timberland Supply Co. Ltd.  
1520 Lorne Street, Kamloops, BC, V2C 1X6  
(250) 372-9561 / (800) 563-5223