



The WH15 and WH20 high-pressure pumps are capable of displacing water at greater pressures for irrigation and spraying, or to higher discharge heights, even when used with long hoses.

Features

- High output (400 litres per minute), high pressure (55 psi)
- Honda GX120 OHV engine
- 38 mm (1.5") suction and discharge ports

Specifications

WH15XK1C1

Pump	Centrifugal
Type	Self-priming
Suction Port Diameter	38 mm /1.5 in.
Discharge Port Diameter	38 mm /1.5 in.
Litres per minute	400
Imp. gal. per minute	88
Litres per hour	24000
Imp. gal. per hour	5280
Total Head	50 m /164 ft.
Suction Head (Total Lift)	8 m /26 ft.
Priming Time @ 5m(16.4 ft.)	40 seconds
Pump Body	Aluminum
Impeller	Cast iron
Honda Engine	GX120K1 4-stroke
Type	OHV, air-cooled, single cyl.
Displacement	118 cc
Lubrication System	Splash type
Governor	Mechanical
Starting System	Recoil
Fuel Tank Capacity	2.5 L /0.55 Imp. gal.
Oil Alert	N/A
Drive Unit Type	Direct couple / mech. seal
Frame Type	Handle type, Steel base
Length	415 mm /16.3 in.
Width	360 mm /14.2 in.
Height	405 mm /15.9 in.
Dry Weight	22 kg. /48.5 lb.

Your Dealer:

Timberland Supply Co. Ltd.
 1520 Lorne Street, Kamloops, BC, V2C 1X6
 (250) 372-9561 / (800) 563-5223