



*The WH15 and WH20 high-pressure pumps are capable of displacing water at greater pressures for irrigation and spraying, or to higher discharge heights, even when used with long hoses.*

### Features

- High output (500 litres per minute), high pressure (61 psi)
- Honda GX160 OHV engine
- 50 mm (2") suction and discharge ports

### Specifications

## WH20XK1JC1

Pump	Centrifugal
Type	Self-priming
Suction Port Diameter	50 mm /2.0 in.
Discharge Port Diameter	50 mm /2.0 in.
Litres per minute	500
Imp. gal. per minute	110
Litres per hour	30000
Imp. gal. per hour	6600
Total Head	50 m /164 ft.
Suction Head (Total Lift)	8 m /26 ft.
Priming Time @ 5m(16.4 ft.)	60 seconds
Pump Body	Aluminum
Impeller	Cast iron
Honda Engine	GX160K1 4-stroke
Type	OHV, air-cooled, single cyl.
Displacement	163 cc
Lubrication System	Splash type
Governor	Mechanical
Starting System	Recoil
Fuel Tank Capacity	3.6 L /0.79 Imp. gal.
Oil Alert	N/A
Drive Unit Type	Direct couple / mech. seal
Frame Type	Handle type, Steel base
Length	425 mm /16.7 in.
Width	375 mm /14.8 in.
Height	405 mm /15.9 in.
Dry Weight	23.5 kg. /52 lb.

### Your Dealer:

**Timberland Supply Co. Ltd.**  
**1520 Lorne Street, Kamloops, BC, V2C 1X6**  
**(250) 372-9561 / (800) 563-5223**