

WX10K1C



Lightweight and portable, these light-duty pumps are designed for pool maintenance, filling water tanks at the cottage or small to mid-size drainage jobs. The WX10 can easily accommodate a standard garden hose (1") – (adapter included).

Features

- Honda GX25 OHC Mini four-stroke engine
- 25.4 mm (1") suction and discharge ports
- Pumps 140 litres per minute (31 Imp. Gal per minute)

Specifications

Pump	Centrifugal
Type	Self-priming
Suction Port Diameter	25.4 mm /1.0 in.
Discharge Port Diameter	25.4 mm /1.0 in.
Litres per minute	140
Imp. gal. per minute	31
Litres per hour	8400
Imp. gal. per hour	1860
Total Head	36 m /118 ft.
Suction Head (Total Lift)	8 m /26 ft.
Priming Time @ 5m(16.4 ft.)	80 seconds
Pump Body	Aluminum
Impeller	Aluminum
Honda Engine	GX25 mini 4-stroke,
Type	OHC, air-cooled, single cyl.
Displacement	25 cc
Lubrication System	Controlled oil mist
Governor	Mechanical
Starting System	Recoil
Fuel Tank Capacity	0.55 L /0.12 Imp. gal.
Oil Alert	N/A
Drive Unit Type	Direct couple / mech. seal
Frame Type	Handle type, Steel base
Length	325 mm /12.8 in.
Width	221 mm /8.7 in.
Height	300 mm /11.8 in.
Dry Weight	6.1 kg. /13.4 lb.

Your Dealer:

Timberland Supply Co. Ltd.
1520 Lorne Street, Kamloops, BC, V2C 1X6
(250) 372-9561 / (800) 563-5223