



Features

- Honda GXH50 four-stroke OHV engine
- 38 mm (1.5") suction and discharge ports
- Pumps 240 litres per minute (53 Imp. Gal. per minute)
- Oil Alert™ is standard

Specifications

WX15CX1C

Pump	Centrifugal
Type	Self-priming
Suction Port Diameter	38 mm /1.5 in.
Discharge Port Diameter	38 mm /1.5 in.
Litres per minute	240
Imp. gal. per minute	53
Litres per hour	14400
Imp. gal. per hour	3180
Total Head	40 m /130 ft.
Suction Head (Total Lift)	8 m /26 ft.
Priming Time @ 5m(16.4 ft.)	110 seconds
Pump Body	Aluminum
Impeller	Aluminum
Honda Engine	GXH50 4-stroke,
Type	OHV, air-cooled, single cyl.
Displacement	49 cc
Lubrication System	Splash type
Governor	Mechanical
Starting System	Recoil
Fuel Tank Capacity	1.2 L /0.26 Imp. gal.
Oil Alert	Standard
Drive Unit Type	Direct couple / mech. seal
Frame Type	Handle type, Steel base
Length	325 mm /12.8 in.
Width	275 mm /10.8 in.
Height	375 mm /14.8 in.
Dry Weight	9 kg. /20 lb.

Your Dealer:

Timberland Supply Co. Ltd.
1520 Lorne Street, Kamloops, BC, V2C 1X6
(250) 372-9561 / (800) 563-5223