





The most advanced portable power supply available on the market today, with plenty of smooth, stable electrical power.

### Features

- High-tech 2 layer enclosure and unique muffler design offers whisper quiet operation – 58 dB(A) at rated load/48 dB(A) at 25% load
- Reliable Honda GX200 OHV four-stroke engine
- Dependable 12 volt DC electric start with enclosed low maintenance battery
- Hi Tech inverter circuitry provides ultra clean electrical power for sensitive electronic equipment
- Eco-Throttle™ continuously matches engine speed to electrical load, offering excellent fuel efficiency with up to 20 hours continuous running time and reduced noise and vibration
- Convenient circuit breaker construction
- Internal circuit protection is built into the inverter
- 12 VDC battery charging at 8.3 amps
- Battery charge cable is standard
- One lever on/off ignition and fuel control
- 13 litre tank gives 7.2 hours continuous operation at rated load/20 hours continuous at 25% load

### Specifications

## EU3000iS CA

Generator Type	Inverter
Maximum AC Output (Watts)	3000
VAC Voltage Available	120
Maximum Continuous AC Output (Watts)	2800
Max. Rated AC Amperage @ 120 V / 240 V	23.3 / -
Ground Fault Circuit Interrupter (GFCI)	-
Frequency (Hertz)	60
Automatic Voltage Regulator	std.
DC Output (Volts / Amps)	12/8.3
Honda Engine	GX200
Type	OHV, 4-stroke, Air-cooled
Displacement	196 cc
Starting System	Electric / Recoil
Low level Oil Alert™ System	std.
Auto Throttle	Eco-Throttle™ std.
Remote start capability	no
Fuel Tank capacity (litres)	13
Transport Wheels	optional 4-wheel P/N 06423-ZS9-T30 or 06424-ZS9-000AH (front swivel and locking wheels)
Lifting Hook	-
Battery	std (P/N 31500-HN1-003)
Approximate running Time / Tankful (hrs.)	7.2** / 20***
Rated Fuel Consumption (litres / hour)	1.78**
Noise Level dB(A) (1.5 metres to 7 metres)	58** / 48***
Length	655 mm (25.8 in.)
Length - with handles folded	-
Length - with handles	-
Width - without handles and wheels	445 mm (17.5 in.)
Width - with wheels	-
Height - without lift-hook	555 mm (21.8 in.)
Height - with lift-hook	-
Dry Weight	59 kg (130 lb.)
Common Duplex Receptacle Specifications	 23.3 amps/120 volts continuous is available as combined total from these two AC receptacles. Maximum of 20 amps is available from a single receptacle.
DC Receptacle Specifications	 8.3 amps/12 VDC is available from this receptacle. Important Note: AC and DC output cannot be used simultaneously. DC system uses floating N (Neutral) type.

DC charging cable



std

High Capacity 120/240 VAC Twist Lock Receptacle Specs

