

**HONDA****Power****Equipment**



*This high output generator offers the best electrical standby power. The dual voltage inverter configuration allows you to power up appliances that require 120 or 240 volts. The new EU6500isC Dual Voltage Inverter generator features rugged transport wheels and an innovative fold-down handle as standard design features. The EU6500isC incorporates a number of unique design features and technological innovations that give it a low-noise rating of 60 dB(A).*

## Features

- 6500 Watts (45.8/22.9 A) 120/240 V of Honda inverter power
- Super Quiet - 60 dB(A)
- Eco-Throttle™ standard - Runs up to 14 hours on 16.5 litres of fuel
- Convenient electric starting
- Perfect for RV's and home back up power
- Safely powers sensitive electronic equipment
- 120/240 V Selector switch
- Protected by Oil Alert™
- Rugged transport wheels
- Fuel gauge standard
- Optional remote - starter kits available
- Electronic circuit breakers
- i-Monitor LCD readout for performance monitoring and service diagnosis
- Convenient, folding handles

## Specifications

## EU6500isC

Generator Type	Dual Inverter
Maximum AC Output (Watts)	6500
VAC Voltage Available	120/240
Maximum Continuous AC Output (Watts)	5500
Max. Rated AC Amperage @ 120 V / 240 V	45.8/22.9
Ground Fault Circuit Interrupter (GFCI)	-
Frequency (Hertz)	60
Automatic Voltage Regulator	std.
DC Output (Volts / Amps)	-
Honda Engine	GX390K1
Type	OHV, 4-stroke, Air-cooled
Displacement	389 cc
Starting System	Electric / Recoil
Low level Oil Alert™ System	std. (LED display)
Auto Throttle	Eco-Throttle™ std.
Remote start capability	optional
Remote start kit part number info	32380-Z11-810ZA (10 m) 32380-Z11-820ZA (20 m) 32380-Z11-830ZA (30 m)
Fuel Tank capacity (litres)	16.5 (Effective)
Transport Wheels	2-wheel kit std.
Lifting Hook	optional (P/N 06531-Z11-E00ZA)
Battery	std. (P/N 31500-MCR-D02)
Approximate running Time / Tankful (hrs.)	5.1**
Rated Fuel Consumption (litres / hour)	3.24**
Noise Level dB(A) (1.5 metres to 7 metres)	60**
Length	-
Length - with handles folded	850 mm (33.5 IN.)
Length - with handles	1195 mm (47.0 in.)
Width - without handles and wheels	-
Width - with wheels	672 mm (26.5 in.)
Height - without lift-hook	699 mm (27.5 in.)
Height - with lift-hook	716 mm (28.2 IN.)
Dry Weight	115 kg (253.5 lb.) (including battery)
Common Duplex Receptacle Specifications	 40 amps/120 volts continuous is available as combined total from these two AC receptacles. Maximum of 20 amps available from a single receptacle. 

## High Capacity 120/240 VAC Twist Lock Receptacle Specs



This receptacle will supply 30 amps at 120 VAC continuously.



This receptacle will supply 22.9 amps at 240 VAC continuously and 45.8 amps at 120 VAC.